## FloorMate 80



## Specifications:

<u>Engine</u>: 18 HP Kohler Command industrial rated gasoline engine. Equipped with electric start and safety shut down system. \*Electric Motor optional

Mixer: Patented Contra-Blend design, 4 cubic foot capacity, twin ribbon paddles with wiper blades, packing type seal chambers and support bearings on all shafts. Body constructed of twin, interconnected, horizontal drums. Mixer empties without tilting. \*Rubber lined and adjustable packing optional.

<u>Material Pump</u>: #80 Progressive Cavity Pump, Chrome Rotor, Natural Rubber Stator, 4 cubic ft. Wet Material Holding Hopper, Variable Output 0-10gpm with water @ 0 PSI. \*Carbine coated rotor, UHMW liner, pressure gauge optional

<u>Water System</u>: A variety of water systems are available. Contact Strong Manufacturing for water system options.

<u>Hydraulic System</u>: Fixed displacement hydraulic pump, variable speed directional control valve for material pump, fixed speed directional control valve for mixer, 19 Gallon Hydraulic Oil Reservoir.

FloorMate80	Mixer Size	Hopper Size	Yrds3/per hour	Gallons/min
Specifications:	4ft <sup>3</sup>	4ft <sup>3</sup>	6yrds <sup>3</sup>	10

Small unit, big results!

Electric optional

Designed to fit inside standard elevator shafts

Easy operations

Minimum manpower

Strong

2301 University Dr Pine Bluff AR 71603

1-800-238-5042

www.strongmfg.com

