



***THERE IS A DIFFERENCE IN MIXING AND PUMPING EQUIPMENT***  
***"WE PROVE IT EVERYDAY"***

The Complete Solution for all Mixing and Pumping Jobs

Completely mobile, all components mounted on a tandem axle trailer can be towed with a pick-up truck.  
A dependable, efficient machine for installation of spray applied materials, grouting, void filling, mud jacking and undersealing.



***Strong***  
***SprayMate 35D***

***The Complete Solution for Small Mixing and Pumping Jobs***

**Engine**

36hp, Industrial Diesel Engine, Air Cooled.  
*Optional Engines, Contact Strong Manufacturing for other engine options.*

**Mixer**

Patented 6 cubic ft. Double-Drum Mixer, Hydraulically Operated via Mechanical Drive, Counter Rotating Ribbon Paddles, Rubber lined.  
*Options include, Adjustable Packing Chambers and Outboard Bearings. Hydraulically Operated Mixer Door, UHMW liner*

**Material Pump**

#60 Progressive Cavity Design Pump, Chrome Rotor, Natural Rubber Stator, 2.5 cubic ft. Wet Material Holding Hopper with UHMW lining, Variable Output 0-10gpm @0 psi.  
*Options include, Carbide Rotor, 6 cubic ft. Material Blender, Material Hose Pressure Gauge*

**Water System**

300 Gallon Water Tank, Belt Driven Water Pump, Analog Water Meter  
*Options include, Hydraulic Powered High Pressure Washer, Digital Water Meter*

**Hydraulic System**

Variable Displacement Pressure Compensated Piston Pump with Fixed Displacement Gear Pump, 30 Gallon Hydraulic Oil Reservoir  
*Options include, Hydraulic Oil Cooler*

**Air System**

Call for air system.

**Frame**

Made of Tubular Steel, Tandem Axle, 15" Tires, Leaf Spring Suspension, Electric Brakes, Running Lights, Ball or Pintle Hitch

**Dimensions**

Length: 18' Width: 8'2" Height: 8' Weight: 5600lbs.



STRONG MFG. CO. FOLLOWS THE POLICY OF CONTINUOUS  
ADVANCEMENT IN PRODUCT DEVELOPMENT. FOR THIS REASON  
SPECIFICATIONS AND DIMENSIONS ARE FOR REFERENCE ONLY  
AND MAY BE CHANGED WITHOUT NOTICE

**P.O. BOX 8068 • PINE BLUFF, AR 71611**  
**PHONE 1-800-238-5042 • (870) 535-4753**

**FAX (870) 535-4843**

**[www.strongmfg.com](http://www.strongmfg.com)**

**E-MAIL [sales@strongmfg.com](mailto:sales@strongmfg.com)**