



There is a difference in mixing and pumping equipment
"WE PROVE IT EVERYDAY"
GroutMate 420/80



Engine

KUBOTA V1903E, 36hp, Diesel, Water Cooled, Equipped with Full Instrumentation and Safety Shut Down System

Optional Engines, Contact Strong Manufacturing for other engine options.

Mixer

Patented 12 cubic ft. Double-Drum Mixer, Hydraulically Operated via Mechanical Drive, Counter Rotating Ribbon Paddles, Rubber lined.

Options include, Adjustable Packing Chambers and Outboard Bearings. Hydraulically Operated Mixer Door, UHMW liner

Material Pump

#80 Progressive Cavity Design Pump, Chrome Rotor, Natural Rubber Stator, 12 cubic ft. Wet Material Holding Hopper with UHMW lining, Variable Output 0-35gpm @0 psi.

Options include, Carbide Rotor, 12 cubic ft. Material Blender, Material Hose Pressure Gauge

Water System

100 Gallon Water Tank, Manual Discharge Valve, Automatic Shut-off Fill Valve

Options include, Hydraulic Powered Water Pump, Digital Water Meter, Analog Water Meter

Hydraulic System

Variable Displacement Pressure Compensated Piston Pump with Fixed Displacement Gear Pump, Hydraulic Oil Cooler, 45 Gallon Hydraulic Oil Reservoir

Frame

Made of Tubular Steel, Single Axle, 15" Tires, Torsion Suspension, Electric Brakes, Running Lights, Ball or Pintle Hitch

Dimensions

Length: 16' ♦ Width: 6'3" ♦ Height: 9'6" ♦ Weight: 5300lbs.

STRONG MFG. CO. FOLLOWS THE POLICY OF CONTINUOUS ADVANCEMENT IN PRODUCT DEVELOPMENT. FOR THIS REASON SPECIFICATIONS AND DIMENSIONS ARE FOR REFERENCE ONLY AND MAY BE CHANGED WITHOUT NOTICE

P.O.BOX 8068 ♦ PINE BLUFF, AR 71611
PHONE 1-800-238-5042 ♦ (870) 535-4753

FAX (870) 535-4843

www.strongmfg.com

E-MAIL sales@strongmfg.com