

Strong MANUFACTURING

**THERE IS A DIFFERENCE IN MIXING AND PUMPING EQUIPMENT
"WE PROVE IT EVERYDAY"**



Multi-Mate

The Complete Solution for Small Mixing and Pumping Jobs

Engine

8hp industrial rated gasoline engine equipped with recoil start and safety shut down system. Approximately 2 hours run time on one tank of fuel.

Options include: Electric Start.

Contact Strong Manufacturing for other engine options

Mixer

Patented Contra-blend design, 2.5 cubic foot capacity, twin ribbon paddles with wiper blades, packing type seal chambers and support bearings on all shafts. Body constructed of twin, interconnected, horizontal drums. Mixer empties without tilting.

Options include adjustable packing with outboard bearings.

Rubber or UHMW lining.

A variety of water systems are available

Contact Strong Manufacturing for water system options

Material Pump

#60 Progressive Cavity Pump, Chrome Rotor, Natural Rubber Stator, 2.5 cubic ft. Wet Material Holding Hopper, Variable Output 0-10gpm with water @ 0 PSI

Options include, Carbide Coated Rotor, UHMW liner for hopper, Material Hose Pressure Gauge.

Hydraulic System

Fixed displacement hydraulic pump, variable speed directional control valve, 10 Gallon Hydraulic Oil Reservoir.

Frame

Lightweight frame constructed from low carbon steel, equipped with non-marking pneumatic wheels for ease of placement.

Air System

Contact Strong Manufacturing for Air System options

Dimensions

Length: 6'6" ♦ Width: 3'2" ♦ Height: 4'4" ♦ Weight: 750lbs.

Strong MANUFACTURING

STRONG MFG. CO. FOLLOWS THE POLICY OF CONTINUOUS ADVANCEMENT IN PRODUCT DEVELOPMENT. FOR THIS REASON SPECIFICATIONS AND DIMENSIONS ARE FOR REFERENCE ONLY AND MAY BE CHANGED WITHOUT NOTICE

**P.O. BOX 8068 ♦ PINE BLUFF, AR 71611
PHONE 1-800-238-5042 ♦ (870) 535-4753**

FAX (870) 535-4843

www.strongmfg.com

E-MAIL sales@strongmfg.com



Shown with optional Air System

Shown with optional Water Systems