

BIG-GYP-“C”



Applications

- Floor Underlayment
- Floor Topping



Strong
MANUFACTURING
Family Owned and Operated Since 1964

P.O. Box 8068
Pine Bluff, AR 71611
P: (870)-535-4753 (800)-238-5042
F: (870)-535-4843
www.strongmfg.com

SPECIFICATIONS

Engine: Tier 4 final industrial diesel engine, complete with safety switches, hour meter and tachometer, engine cowling with replaceable air filter, 12-volt dc electric start.

Mixer: 8 cubic foot double-drum patented contra-blend mixer, rubber lined, hydraulic powered, chain and sprocket driven paddles, adjustable packing assemblies, and a raised operator platform.

Material Pump: Strong #80 progressive cavity pump. 8 cubic foot holding hopper, UHMW lined, adjustable speed drive, 30 GPM maximum discharge rate.

Material Handling System: Hydraulically powered 8 cubic foot capacity skip bucket, UHMW lined, and capable of conveying material from lowered

Water System: 60-gallon water tank, manual discharge valve, automatic shut-off fill valve options include, hydraulic powered water pump, digital water meter, analog water meter

Frame: Heavy duty rectangular tubing frame, dual 6000-pound torsion axle, with 15" radial tires, electric brakes, safety chains and breakaway switch, all required lighting, pintle, 2" ball & socket hitch, or 2 5/16" ball & socket hitch.

Dimensions: Length: 17' Width: 7' Height: 8'8" Weight: 7,700lbs.

Big-Gyp-"C"	<u>Mixer Size</u>	<u>Hopper Size</u>	<u>Yrds³/per hour</u>	<u>Gallons/min</u>
Specifications:	8ft ²	8ft ²	9yrds ³	30