

# StrongMate F80



## Specifications:

**Engine:** 75 HP Tier 4 Final diesel engine equipped with full instrumentation and safety shut down systems.

**Material Pump:** #80 Progressive Cavity Pump, chrome rotor, natural rubber stator. 50GPM slurry output- 30yrds<sup>3</sup>@50% Cellular- 60yrds<sup>3</sup>@75% Cellular

**Water System:** 110 Gal Holding Capacity

**Air Compressor:** Quincy 40 CFM @ 200 PSI

**Concentrate:** 55gal drum holding stand

**Inverter:** 5000-Watt Industrial power inverter

**Hopper:** 12cuft wet material holding hopper with material splash guard



**Aerix Industries™**  
Advanced Engineered Foam Solutions

### Auto-Foam Generator (AFG)

- 2 GPM water-driven, adjustable, concentrate metering pump.
- Nozzles for various foam output production.
- 20 V electric-driven solution booster pump.
- 4-Gal foam solution surge tank

**All in one, self-contained pump!**

**Tier 4 Final**

**In-Line Foam injection!**

**Aerix Industries  
AFGS Foam  
Generator**

**Strong  
MANUFACTURING**

2301 University Dr  
Pine Bluff AR 71603

1-800-238-5042

[www.strongmfg.com](http://www.strongmfg.com)