

# FillerMate 80



## Specifications:

**Power Supply:** System to include on/off function for mixer and on/off/reverse function for pump. System to include all necessary safety switches and controls for safe operation of system. Wired for 230 V/ 3 Phase/60 Htz or 460 V/3 Phase/60 Htz

**Mixer:** 10 cubic foot double-drum contra blend mixer, rubber lined, direct chain and sprocket drive paddle shafts. Powered by an electric gear motor. Furnished with operator platform for ease of operation

**Material Pump:** Strong #80 progressive cavity pump, holding hopper, single constant speed drive, 30 GPM maximum discharge rate. 2"x50' material hose, Powered by an electric gear motor.

**Water System:** Operator accessible manual on/off 1" water meter with direct reading dial. \*Options include, hydraulic powered water pump, digital water meter

**Frame:** Made of tubular steel, Forklift channels, swivel steel casters as well as detachable workers platform

**Dimensions:** Length: 151" Width: 51" Height: 74" Weight: 2500lbs.

**10 cubic ft  
Mixer!**

**Less than 3,000  
pound**

**240/460V**

**Plant Install  
ready**

**Detachable  
Workman's  
Platform!**

**Strong**  
**MANUFACTURING**

2301 University Dr  
Pine Bluff AR 71603

1-800-238-5042

[www.strongmfg.com](http://www.strongmfg.com)