OORMATE30E

GI GI

Features & Applications

Sint Sint

- **Floor Topping**
- . Self-Leveling
 - **Fully Electric**





P.O. Box 8068 Pine Bluff, AR 71611 P: (870)-535-4753 (800)-238-5042 F: (870)-535-4843 www.strongmfg.com

SPECIFICATIONS

Engine: Mixer power to consist of 110V, 15A (standard wall outlet). 1.5HP electric motor (with a kill switch). Material pump power source to be 240V single phase, 30A. 7.5 HP electric motor (with an e-stop).

<u>Mixer</u>: Patented Contra-Blend design, 5 cubic foot capacity, twin ribbon paddles with wiper blades, packing type seal chambers and support bearings on all shafts. Body constructed of twin, interconnected, horizontal drums. Mixer empties without tilting. *Rubber lined and adjustable packing optional.

<u>Material Pump</u>: Strong #80 chain driven progressive cavity pump with half-length rotor and stator. 5ft3 holding hopper. Adjustable output rate, 0-30 GPM. *See options list for full length rotor stator option. Pressure increases for higher vertical distances

<u>Water</u> <u>System</u>: A variety of water systems are available. Contact Strong Manufacturing for water system options.

<u>Frame</u>: Lightweight frame constructed from low carbon steel, equipped with casters for ease of placement.

Dimensions: Length: 7' Width: 3' Height: 4'8" Weight: 1,350lbs.

FloorMate80E	Mixer Size	Hopper Size	Yrds3/per hour	<u>Gallons/min</u>
Specifications:	5ft ²	5ft ²	9yrds ³	0-30