

GeoFlow



Specifications:

Engine: Tier 4 Final Industrial Diesel Equipped with Full Instrumentation and Safety Shut Down System **Optional Engines, Contact Strong Manufacturing for other engine options.*

Mixer: Patented 27 cubic ft. Double-Drum Mixer, Hydraulically Operated via Mechanical Drive, Counter Rotating Ribbon Paddles, Rubber lined Equipped with Adjustable Packing Chambers and Outboard Bearings. Raised operator platform. **Options include, Hydraulically Operated Mixer Door, UHMW liner*

Material Pump: #80 Progressive Cavity Design Pump, Chrome Rotor, Natural Rubber Stator, 12 cubic ft. Wet Material Holding Hopper with UHMW lining, Variable Output 0-35gpm @0 psi. **Options include, Carbide Rotor, 12 cubic ft. Material Blender, Material Hose Pressure Gauge*

Water System: ½" water meter with manual discharge valve, Automatic Shut-off Fill Valve **Options include, Hydraulic Powered Water Pump, Digital Water Meter, Analog Water Meter*

Hydraulic System: Variable Displacement Pressure Compensated Piston Pump with Fixed Displacement Gear Pump, Hydraulic Oil Cooler, 45 Gallon Hydraulic Oil Reservoir

Frame: Made of Tubular Steel, Tandem Axle, Torsion Suspension, Electric Brakes, Running Lights, Ball or Pintle Hitch. **Optional: Hose Reel*

Dimensions: Length: 14'8" Width: 6'3" Height: 8'6" Weight: 4900lbs



**Bulk Bag
compatible!**

Tier 4 Final

**Pump through
hose reel
capable!**

**No need to break
bags!**

**Big mixes,
excellent pours**

Strong
MANUFACTURING

2301 University Dr
Pine Bluff AR 71603

1-800-238-5042

www.strongmfg.com