



Features & Applications

- . Floor Underlayment
- . #100 Progressive Cavity
 - . 12cuft Mixer



Strong
MANUFACTURING
Family Owned and Operated Since 1964

P.O. Box 8068 Pine Bluff, AR 71611 P: (870)-535-4753 (800)-238-5042 F: (870)-535-4843

www.strongmfg.com

SPECIFICATIONS

Engine: Industrial Tier4 final 99hp equipped with full instrumentation and safety shut down systems.

*Optional engines contact strong manufacturing for other engine options

Mixer: Patented 12cuft double-drum mixer, hydraulically operated via mechanical drive, counter rotating ribbon paddles, rubber lined.

Material Pump: #100 Progressive cavity design pump, chrome rotor, natural rubber stator, 12cuft wet material holding hopper with UHMW lining, Variable output 0-100gpm @0 psi.

Material Handling System: 12cuft skip loading system with hydraulic lift and dump

<u>Water System</u>: 60-gallon water tank, manual discharge valve, automatic shut-off fill valve options include, hydraulic powered water pump, digital water meter, analog water meter

Frame: Made of tubular steel, duel axle, 19." tires, electric brakes, running lights, ball or pintle hitch

Dimensions: Length: 19'6" Width: 7'3" Height: 10'7" Weight: 12,000 lbs.

Placer	Mixer Size	Hopper Size	Yrds3/per hour	Gallons/min
Specifications:	12ft²	12ft ²	30yrds ³	100