

Rear Skip Placer



Specifications:

Engine: Diesel, 99hp, water cooled, equipped with full instrumentation and safety shut down system optional engines, contact strong manufacturing for other engine options.

Mixer: Patented 12 cubic ft. double-drum mixer, hydraulically operated via mechanical drive, counter rotating ribbon paddles, rubber lined. options include, hydraulically operated mixer door, UHMW liner, adjustable packing chambers and outboard bearings.

Material Pump: #100 Progressive cavity design pump, chrome rotor, natural rubber stator, 12 cubic ft. wet material holding hopper with UHMW lining, variable output 0-100gpm @0 psi. options include, carbide rotor, 12 cubic ft. material blender, material hose pressure gauge

Material Handling System: 12 cubic ft. skip loading system, hydraulic lift and dump

Water System: 60-gallon water tank, manual discharge valve, automatic shut-off fill valve options include, hydraulic powered water pump, digital water meter, analog water meter

Hydraulic System: Variable displacement hydrostatic transmission with fixed displacement gear pump, hydraulic oil cooler, 60-gallon hydraulic oil reservoir

Frame: Made of tubular steel, dual axle, 16" tires, torsion or leaf spring suspension, electric brakes, running lights, ball or pintle hitch

Dimensions: Length: 19' Width: 8'2" Height: 9'10" Weight: 10,500lb

Same great
pump, All new
Look!

Tier 4 Final

Minimal job site
space!

Lower worker
height!

Expanded
Workman's
Platform!

Strong
MANUFACTURING

2301 University Dr
Pine Bluff AR 71603

1-800-238-5042

www.strongmfg.com

Placer	Mixer Size	Hopper Size	Yrds ³ /per hour	Gallons/min
Specifications:	12ft ²	12ft ²	30yrds ³	100